



SAFETY DATA SHEET

Base Oil Ultra-S 8 (250 Neutral)

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	Base Oil Ultra-S 8 (250 Neutral)		
APPLICATION	Lubricating Oil Base Stock		
SUPPLIER	MANUFACTURER	S-OIL CORPORATION 63B/D, 60 Yoido-dong, Yongdungpo-gu, Seoul 150-607 Korea	
EMERGENCY TELEPHONE	+82-52-231-2256		

2 HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION IN ACCORDANCE WITH GHS

Physical and Chemical Hazards	Not classified.
Human health	Not classified.
Environment	Not classified.

LABEL IN ACCORDANCE WITH GHS

Not classified.

PRECAUTIONARY STATEMENTS

P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P405	Store locked up.

3 COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE NAME	CAS NO.	PURITY (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	100

4 FIRST-AID MEASURES

GENERAL INFORMATION

Contact physician if discomfort continues.

INHALATION

Move the exposed person to fresh air at once.

If respiratory problems, artificial respiration/oxygen.

INGESTION

Get medical attention immediately!

Immediately rinse mouth and provide fresh air.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water.

Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

NOTE! Use air-supplied respirators to protect against gases/fumes. Use water SPRAY only to cool containers! Do not put water on leaked material.

UNUSUAL FIRE & EXPLOSION HAZARDS

N/A.

SPECIFIC HAZARDS

When heated and in case of fire, corrosive vapours/gases may be formed.

Base Oil Ultra-S 8 (250 Neutral)

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not allow ANY environmental contamination. Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Collect with absorbent, non-combustible material into suitable containers. Transfer to a container for disposal.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Wear full protective clothing for prolonged exposure and/or high concentrations. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Keep upright. Keep away from food, drink and animal feeding stuffs. Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide sufficient ventilation during operations which cause vapour formation.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator. Wear mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

Chemical resistant gloves required for prolonged or repeated contact.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Provide eyewash station.

HYGIENE MEASURES

Wash hands after contact. Promptly remove any clothing that becomes contaminated. DO NOT SMOKE IN WORK AREA!

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Viscous liquid
COLOUR	Clear
BOILING POINT (°C)	N.A.
RELATIVE DENSITY	0.847 @ 15°C
VAPOUR PRESSURE	N.A.
VISCOSITY	7.0 - 7.5 cSt @ 100°C (ASTM D 445) 42.0 - 55.0 cSt @ 40°C (ASTM D 445)
FLASH POINT (°C)	240 ~ 260°C (ASTM D 92)

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide (CO). Carbon dioxide (CO₂). Aldehydes. Ketones Nitrous gases (NO_x). Sulphurous gases (SO_x).

Base Oil Ultra-S 8 (250 Neutral)**11 TOXICOLOGICAL INFORMATION**

TOXIC DOSE 1 - LD 50 >5000 mg/kg (oral rat)
TOXIC DOSE 2 - LD 50 >5000 mg/kg (dermal/rabbit)

INHALATION

Not relevant at normal room temperatures. When heated, irritating vapours may be formed.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

No specific health warnings noted.

EYE CONTACT

No specific health warnings noted.

HEALTH WARNINGS

Observe good chemical hygiene practices.

ROUTE OF ENTRY

Ingestion. Skin and/or eye contact.

MEDICAL SYMPTOMS

Diarrhoea. Nausea, vomiting.

12 ECOLOGICAL INFORMATION

LC 50, 96 Hrs, FISH mg/l >1000
EC 50, 48 Hrs, DAPHNIA, mg/l >1000
IC 50, 72 Hrs, ALGAE, mg/l >1000

MOBILITY

The product is insoluble in water and will spread on the water surface.

BIOACCUMULATION

Will not bio-accumulate.

DEGRADABILITY

The product is not readily biodegradable.

ACUTE FISH TOXICITY

Not considered toxic to fish.

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

Dispose of waste and residues in accordance with local authority requirements.

DISPOSAL METHODS

Incinerate with provision for removal of effluent gases by scrubber.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

EINECS No. : 265-157-1

CLASSIFICATION IN ACCORDANCE WITH EC 1272/2008

Not classified

CLASSIFICATION IN ACCORDANCE WITH 67/548/EEC

Not classified

16 OTHER INFORMATION**ISSUED BY**

S-OIL

REVISION DATE 18.04.2011

REV. NO./REPL. SDS GENERATED rev.2

Base Oil Ultra-S 8 (250 Neutral)**SAFETY DATA SHEET STATUS**

Temporarily approved for use for 3 months.

DATE 18.04.2011**RISK PHRASES IN FULL**

R65 Harmful: may cause lung damage if swallowed.

HAZARD STATEMENTS IN FULL

H304 May be fatal if swallowed and enters airways.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.